Burch



Repeats Not Shown to Scale.

Stellar

Meets or exceeds all ACT® Standards

Made in the USA Sunbrella Contract Seating Fabric Bleach Cleanable Indoor / Outdoor FR Free – Compliant with CAL AB 2998 PFAS Free





Fabric Specifications

| Content | 69.5% Sunbrella Acrylic, 30.5% Sunbrella Polyester |
|-----------------|---|
| Finish | PFAS Free Soil and Stain Repellent |
| Backing | Acrylic |
| Weight | 17.6 oz/lin yd |
| Width | 54" |
| Roll Size | 55 yards |
| Ends/Picks | 169/96 |
| Repeat | H - 9.47" V - 8.00" |
| Directional | Yes |
| Railroaded | Yes |
| Made in the USA | Yes |

Additional Attributes

| FR Free | Yes |
|-------------|-----|
| HPD on File | Yes |
| PFAS Free | Yes |

Certifications

Greenguard Gold Certified Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

* Cleaning information is offered for general guidance and is not a guarantee. The use of certain cleaning agents can be harmful to the surface appearance and lifespan of a product. Burch Fabrics assumes no responsibility for damage to a product resulting from lack of cleaning, improper cleaning or the misuse of cleaning agents. Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to materials and cause permanent damage. Burch Fabrics cannot be held responsible for dye transfer caused by external contaminants.

Performance Characteristics

| Abrasion Resistance ASTM D4157 | 80,000 * double rubs |
|-----------------------------------|-------------------------------------|
| Brush Pill ASTM D3511 | Class 4 |
| ensile Strength ASTM D5034 | Warp: 344.1 lbs Fill: 451.7 lbs. |
| ear Strength ASTM D2261 | Warp: 71.4 lbs. Fill: 87.7 lbs. |
| eam Slippage ASTM D4034 | Warp: 35.4 lbs. Fill: 44.7 lbs. |
| Colorfastness to Crocking AATCC 8 | Dry: 5.0 Wet: 5.0 |
| Colorfastness to Light AATCC 16 | 2,000 Hours Class 4 |

Flammability**

| CAL TB 117-2013 | Passes |
|-----------------|---------|
| NFPA 260 | Class 1 |
| UFAC | Class 1 |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.